Application No.: 10/656,276 Examiner: Jared FUREMAN

Art Unit: 2876

LIST OF CURRENT CLAIMS

1. (Currently Amended) A 7-in-1 card reader for a PCMCIA interface, said card reader comprises:

a cartridge having a shape in coincidence with an insertion slot of said PCMCIA interface, and being provided therein with an electric connecting circuit;

a first connecter of a specification in coincidence with that of said PCMCIA interface, being fixed on a front side of said cartridge to connect with said electric connecting circuit;

a second <u>first</u> connecter <u>module</u> provided on a <u>read rear</u> end of said cartridge to connect with said electric connecting circuit, and having a plurality of insertion slots for memory cards of specifications including those of CF, MD, MMC, MS and SD memory cards on a side thereof other than another side connecting with said electric connecting circuit, connecting pins are provided at said insertion slots to connect with said connecting circuit;

a third second connecter module provided on said read rear end of said cartridge to connect with said electric connecting circuit, and having an insertion slot for memory cards of specifications including those of SM and XD memory cards on a side thereof other than said another side connecting with said electric connecting circuit;

thereby a card reader is formed for connecting an electric device and for inserting therein and connecting thereto memory cards taken among those of seven specifications, that is to say, those of CF, MD, MMC, MS, SD, SM and XD memory cards through said PCMCIA interface as well as for proceeding to data reading, exchanging and transferring with said electric device.

2. (Currently Amended) The 7-in-1 card reader for a PCMCIA interface as in claim 1, wherein one of said insertion slots on said second <u>first</u> connecter <u>module</u> is

Application No.: 10/656,276

Examiner: Jared FUREMAN

Art Unit: 2876

common for an MMC memory card and an SD memory card, said insertion slot is provided on an inner side thereof with a channel with a width and a thickness in coincidence with those of an MMC memory card and an SD memory card to prevent

wrong insertion of a memory card.

3. (Currently Amended) The 7-in-1 card reader for a PCMCIA interface as in claim 1, wherein one of said insertion slots on said second first connecter module is common for a CF memory card and an MD memory card, said insertion slot is provided on an inner side thereof with a channel with a width and a thickness in coincidence with those of an CF memory card and an MD memory card to prevent wrong insertion of a memory card.

- 4. (Original) The 7-in-1 card reader for a PCMCIA interface as in claim 1, wherein said first connecter is connected with said connecting circuit by using said connecting pins, a coupling part provided on a side of said first connecter other than said another side connecting with said connecting circuit forming inserting connection with said PCMCIA interface; said cartridge has an upper cover and a lower cover to envelop a part of a main body of said connecting circuit and a part a main body of said first connecter to expose said coupling part of said first connecter at said front side of said cartridge.
- 5. (Currently Amended) The 7-in-1 card reader for a PCMCIA interface as in claim 1, wherein said cartridge is provided on a rear part thereof with a cover to envelop main parts of said second first and third second connectors connector modules.
- 6. (Currently Amended) The 7-in-1 card reader for a PCMCIA interface as in claim 1, wherein said cartridge is provided on a rear part thereof with a cover to envelop

Application No.: 10/656,276 Examiner: Jared FUREMAN

Art Unit: 2876

main parts of said second <u>first</u> and <u>third</u> <u>second</u> <u>eonnecters</u> <u>connector modules</u>, said cover is further provided with indicating lights connecting respectively to said insertion slots of said second and third connecters; said indicating lights show states of operation of memory cards in said insertion slots.